Design

INDEX

INDEX TO VOL. I, DESIGN SECTION

(Corrected to include A.L.s. 1 and 2.)
See Introduction to the B Design Leaflets, paras. 2 and 3.

All requirements apply to both hormal and ac	Topatr	caccg	ory c	rerobrem	co am	000		
otherwise stated							B.1	9
Cockpit speed restriction notice, not required on a	ecrobat	tic cate	gory :	aeroplan	es		A.1	2
							B.2	4
C.P. Forward factor of 9							B.2	3
C.P. Forward factor of 9 (engine mounting)							B.3	4
Flight trials, diving tests	. 59						F.3	3
Flight trials, looping and rolling							F.3	5
Flight trials, official, special safety precautions .				mining when	. Dame		F.1	9
Flight trials, official, special safety precautions .			-	10.0 TO		rich .	F.2	9
Flight trials, spinning tests				5.5			F.3	4
Inverted flight, high negative incidence				** 8		et tu	B.2	11
Radiator tests with revised C.P. Forward factor				** 2			D.4	11
Range of airspeed indicator	9 .						E.1	6
Safety harness							E.3	2
Tank tests with revised C.P. Forward factor .							D.2 and	,
							D.3	10
Terminal velocity dive							B.2 Z.3	18
Toe straps for rudder bars								
Windmills for generators to be suitable for T.V.	dives .		• •				E.2	15
Wing stiffness					• •		Z.7	3

Advertising banners—see Towing.

AERIALS:-								
Stressing requirements								
Strength of attachments	is only	1980	10.10	 		 SA, TIN	B.3	19
Strength of aerial			4.1	 		 	E.5	3
Other requirements							70	01
Attachment of aerial weights				 10 3000	1000	of terms	Z.3	21
						 10.4	E.5 B.5	10
Welding of attachments		• •	2.7	 • •		 	D.3	10
AILERONS (see also ALL COMPO	NEN	TS) :-						
Stressing requirements								

Stressing requirements										73.0	-
Mass-balance arms			4.40	1000		* *				B.3	7
Stressing cases				200			an in la			B.3	1
Tail-to-wind case			4.4			* *				B.3	13
Other requirements										77.	10
Fabric and stringing							4.4			B.5	12
Fasteners for inspection	doors						** *	* *		Z.3	17
Flutter, prevention of										B.5	1
Flutter, prevention of,	ailerons	s with	trailin	g edge	tabs					B.5	1
Locking of controls											12
Mass-balance											1
Maximum upward setti	ng of F	rise ty	pe aile	erons						B.5	3
Prevention of aileron in	stabilit	ty				1.5			100.000	B.5	3
irscrew requirements								2012 1		B.8	- in
a a company pro	****	3.573.777	c EOI	TATTS	T ADD	TCAD	TT TO	lo n			

Airscrew requirements	B.8	
ALL COMPONENTS, REQUIREMENTS EQUALLY APPLICABLE TO:-		
Aluminium alloy sheet, bending of	Z.3	6
Castings	B.5	11
Drilling and sweating tubes to T.2	Z.3 B.3	16
Duplicate wires	13.0	10